

液压搬运车



标准型



不锈钢型



电子秤液压搬运车

类型	标准型	标准型	快速起升	低放型	低放型	不锈钢型
型号	DF20	DF30	ACF20	AC-Low-51	AC-Supper Low	ACS20
额定载重(kg)	2000	3000	2000	1500	1000	2000
起升范围(mm)	85~200 / 75~190			51~165	35~90	1150 / 1220
货叉长度(mm)	800/900/1000/1100/1150/1220			1150/1220	1120	540/685

型号	SAC-N20H	SAC-N20L
额定载重(kg)	2000	2000
起升范围(mm)	88~200	76~190
货叉长度(mm)	1150/1220	
备注	自带打印功能	

液压平台车



TF系列



TG系列



TFD系列



ETF系列(电动)

型号	TF15	TF30	TF50	TF75	TF100	TG50	TG100	TFD35	ETF30	ETF50
载重(kg)	150	300	500	750	1000	500	1000	350	300	500
台面最低高度mm	220	285 / 340	285 / 340	420	380	286	360	355	290	440
台面最大高度mm	720	880	880	990	990	915	1360	1300	880	1025
台面尺寸mm	700×450	815×500 / 850×500		1000×510	1016×510	1600×810	2035×750	910×500	820×500	1010×520

堆高车



半电动堆高车

SPN1016G / SPN1025G / SPN1035G



电动托盘搬运车

LPT15(AC) / LPT22(AC)



半电动平衡重堆高车

SPN0516-B / SPN0525-B



全电动堆高车

CS1232 / CG1645AC-EPS

型号	SPN1016G	SPN1025G	SPN1035G	LPT15(AC)	LPT22(AC)	SPN0516-B	SPN0525-B	CS1232	CG1645AC-EPS
最大承载kg	1000			1500	2200	500		1200	1600
货叉最低高度mm	85			85	75		85		
提升最大高度mm	1600	2500	3500	120	1600	2500	3115	4500	

主要用于机械加工行业中铁屑和工业垃圾的装卸和搬运，常用有普通铁屑车和不锈钢铁屑车两种。普通铁屑车采用冷轧钢板为材料，适合一些对车身要求不高的场合；不锈钢铁屑车采用不锈钢为材料，耐油污、成本高，适用于一些特殊场合。



型号	MTX-02
规格	W1000×D600×H870
承重	500kg



型号	MTX-03
规格	W1200×D700×H970
承重	500kg



不锈钢铁屑车



型号	TX-01
规格	W960×D1280×H1060
承重	1000kg



型号	MTX-01
规格	W960×D1280×H1060
承重	800kg



型号	TX-02
规格	W1000×D800×H1150
承重	2000kg



型号	TX-03
规格	W1000×D800×H800
承重	2000kg

